

S 44

Safety vacuum cleaner with automatic filter cleaning system, 42 l, class L

Order no. 444146

GTIN 4030293194960

- + The high-performance turbine ensures both a high suction capacity and a high vacuum. The outcome is an excellent extraction result
- + Continuous automatic flat filter cleaning ensures no loss of suction
- + The flat-fold filter with Teflon coating / nanocoating allows optimum use of the tank volume
- + With permanent socket and electronic automatic on/off switch
- + The flow rate control via the rotary switch minimises possible vacuums on the surface during intermediate and finish sanding
- + Suitable for wet vacuuming: with electronic liquid level control
- + Soft start stops any voltage peaks at the start and the run-on feature (15 sec. overrun) empties any remaining dust in the vacuum hose
- + Double-walled sturdy container with integrated grip recess for emptying the container easily
- + Equipped with large wheels and two swivel guide rollers made of metal
- + Separate motor air cooling duct with coarse dirt filter. Protects the turbine against the ingress of ambient air and thereby extends the service life. (Fine dust filter PES available as an accessory)
- + Simple filter change without removing the suction head
- + With hose retainer and expander for easy, quick securing of the power cable
- + With 4 clamping loops (2 on each side) for attaching straps and a giraffe holder
- + Safety vacuum cleaner, approved for dust class L, suitable for all dust with OEL value $>1 \text{ mg/m}^3$
- + Suitable for increased stress when used commercially. Ideal for cleaning work in offices, storage rooms, workshops and vehicles. Smaller electric power tools, e.g. palm sander, delta sander, random-orbit sander, jigsaws, are primarily used for extraction work. Tools which produce fairly low amounts of dust



Technical data

Power consumption	1400 W
Vacuum cleaner flow rate	4500 l/min
Max. vacuum	25000 Pa
Filter surface area	5000 cm ²
Tank volume	42 L
Liquid capacity	26 L
Equipment socket	Yes
Cable length	7.5 m
Dimensions WxLxH	565 x 385 x 605 mm
Weight	16 kg

Standard equipment

- 1 Suction hose with auxiliary air control (445037)
- 1 PES flat folded filter (445118)
- 1 Disposal bag (445061)
- 2 Extension pipe
- 1 Elbow (445010)
- 1 Floor nozzle (445509)
- 1 Crevice nozzle (385530)
- 1 Upholstery nozzle (385549)
- 1 Round brush (385646)
- 1 Adapter (445029)
- 1 Expander
- 2 Hose clip