

BSE 14-3 100

Burnishing machine TRINOXFLEX

Order no. 433411

GTIN 4030293187177



- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing and pipe belt sanding
- + Variably adjustable burnishing attachment, allows working close up to the edge, also suitable for narrow rollers, incl. edge guide
- + Tool-free grinding tool change via a patented quick-change system
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Adjustable guard: for sanding tools up to \varnothing 125 mm
- + Spindle lock
- + For optimum finishing of various materials, for burnishing, texturing, polishing, brushing, smoothing, de-rusting and deburring steel and stainless steel surfaces



Technical data

Power consumption	1400 W
Power output	880 W
Voltage	230 V
Frequency	50/60 Hz
Brush diameter	125 mm
Brush width	100 mm
No-load speed	1000 - 3500 rpm
Tool fixture, brush sander	19mm
Cable length	4.0 m
Dimensions WxLxH	320 x 210 x 195 mm
Weight	2.9 kg

Standard equipment

1 Sanding attachment, burnishing (433462)