

MXE 1000 + WR2 120

1010 watt 1-speed mixer with accelerator trigger switch

Order no. 495883

GTIN 4030293224445

- + Large, rugged single-speed gear unit with optimum gear ratio for high torque
- + Full-wave electronic control: with soft start, temperature monitoring, overload protection and accelerator switch - for a controlled run-up to the optimum mixing speed. Sustained power in all speed ranges
- + On/off switch with lock and protection at power interruption. Ideal for stationary operation in a mixing station
- + The flexible rubber sleeve over the on/off switch prevents the ingress of dirt. No malfunctions caused by jammed switches
- + Ergonomic handles on the drive unit: low weight, fatigue-free arm posture and upright body posture allow comfortable, ergonomic operation
- + Four corner guards with rubber buffer provide secure storage during transportation and offer protection against shocks and impacts at the building site
- + Protective cap above the motor housing guides the cooling air flow and prevents the ingress of splashing water
- + For mixed applications up to 40 kg
- + Proven standard mixer is ideal for users operating mainly in the low speed range
- + With mixing paddle WR2 for mixture: pasty to tough. Tile adhesive, grout, filler compound, adhesive, finished plaster, adhesive mortar, ...



Technical data

| | |
|-----------------------------|--------------------|
| Power consumption | 1010 W |
| Power output | 550 W |
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Max. mixing basket diameter | 120 mm |
| Tool holder, mixer | M14 |
| No-load speed, 1st gear | 0 - 780 rpm |
| Clamping collar diameter | 53 mm |
| Cable length | 4.0 m |
| Dimensions WxLxH | 405 x 215 x 340 mm |
| Weight | 4.5 kg |

Standard equipment

- 1 Helix paddle WR2 (368881)
- 1 Open-ended wrench SW 19 (439967)
- 1 Open-ended wrench SW 22 (439975)