
## this is proformance



## CHE 2-28 SDS-plus

Universal rotary hammer drill, 2,5 kg, SDS-plus Order no. 413666 GTIN 4030293177130



- Hammer drilling
- Max. drilling range up to 28 mm in concrete
- 1 Ideal for drilling and hammer drilling, diameters from 4-18 mm in masonry and concrete for dowel fixings or through-holes.
- For light-duty chiselling work when removing plaster and tiles
- Rotation stop for chiselling
- Clockwise/anti-clockwise rotation with switchover via carbon brush reverser. As a result, almost identical torque in both directions of rotation
- Depth limit gauge: for precision drilling
- Accelerator switch with lock-on function





## **Technical data**

Power consumption	800 W
Voltage	230 V
Frequency	50/60 Hz
Tool holder, drill and chisel	SDS-plus
Max. single impact energy	2,7 J
No-load speed	0 - 1300 rpm
No-load blows	0 - 4000 1 rpm
Max. drilling diameter in concrete	28 mm
Max. drilling diameter in wood	30 mm
Max. drilling diameter in steel	13 mm
Cable length	4,0 m
Dimensions WxLxH	360 x 85 x 200 mm
Weight	2,65 kg

## Standard equipment

- 1 Handle (417661)
- 1 Depth stop (417769) 1 Carrying case L-BOXX® (414085) 1 Case insert (414042)