

# GE 7 + MH-T + SH

Giraffe® wall and ceiling sander with interchangeable head system

Order no. 494542

GTIN 4030293224070

- + Very handy, light-weight machine with optimum ease of operation. Provides comfortable and ergonomic working conditions
- + Fitted with innovative interchangeable head system. Sanding heads are attached and removed with a click
- + Triangular sanding head with a 4 mm stroke, ideal for sanding corners and edges. The orbital movement guides the abrasive directly up to the edge. The rotation follows the movement of the tool, without interruption of work
- + Reliable force transmission and high flexibility thanks to the flexible drive shaft from. For decades established "FLEX technology". Thanks to this design principle the weight on the head of the Giraffe is reduced to a minimum. This facilitates handling.
- + Electronic: controlled constant speed, soft-start, overload protection and speed selection with adjuster wheel
- + Easy guiding: by optimal balance between motor and sanding head
- + Effective dust extraction from between the brush ring and the sanding pad prevents clogging of the abrasive and promotes a dust-free working environment
- + Option of connecting the FLEX safety vacuum cleaners to the FLEX clip-system on the guide tube
- + Dust-proof on/off switch
- + Very flexible thanks to an optional 500 mm extension (accessory) for high rooms, can be attached without any tools
- + According to the assortment of sanding paper ideally suited for sanding plaster boards, solid styropor insulation slabs, preparation for painting
- + Very large areas and rooms up to 3.40 m in height can be processed thanks to the optional application of the GM 340
- + The innovative, textile transport system allows the machine and accessories to be transported effortlessly. The Giraffe® does not have to be mounted and is immediately ready for use
- + Gimbal-mounted sanding head provides high flexibility and optimum adjustment for sanding walls and ceilings.



## Technical data

Power consumption	710 W
Power output	410 W
Voltage	230 V
Frequency	50/60 Hz
Backing pad diameter	225 mm
No-load speed	1100 - 1650 rpm
Orbit rate, no load MH-T	3800 - 5700 1 rpm
Orbit rate, no load MH-X	3100 - 4600 1 rpm
Head angle of inclination	100°
Tool holder, wall and ceiling sander	hook and loop
Cable length	5,0 m
Length	1520 mm
Weight	4,2 kg

## Standard equipment

- 1 Triangular sanding head (457191)
- 1 Clip-on quick clamping ring red (406023)
- 1 Antistatic suction hose with auxiliary air control (406708)
- 1 Carrying bag (408867)