

XFE 7-15 150

Roto random orbit polisher

Order no. 418080

GTIN 4030293180567



- + 15 mm orbit for high efficiency
- + Free-spinning drive for hologram-free finishing
- + Low heat generation on the surface makes it ideal for temperature-sensitive paints
- + Powerful 710 watt motor with highly-efficient ventilator for optimum cooling
- + Optimised air flow for optimum cooling of motor and gear. No annoying exhaust air for the user
- + Continuous speed control trigger: for a gentle start and a lock-on for continuous operation
- + VR microprocessor control: with tachogenerator constant speed control, soft start, continuous speed control trigger, restart protection after power failure, overload protection, temperature monitoring and speed selection
- + Flat gear head reduces distance to the surface. The machine can therefore be operated safely in any position.
- + Counterweight for smoother operation
- + Cushioned special hook and loop pad for polishing.
- + Grip hood: ergonomically shaped with SoftGrip. The machine can be controlled with precision and is always comfortable yet secure to hold.
- + With rubberised resting bar for safe setting down
- + 4 metres PUR H05-BQF cable: wear-resistant, flexible and highly resistant to cuts and abrasions



Technical data

| | |
|--------------------------|-------------------|
| Power consumption | 710 W |
| Power output | 420 W |
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Max. polishing disc size | 160 mm |
| Max. support plate size | 150 mm |
| Polishing stroke | 15 mm |
| No-load speed | 1500 - 4500 rpm |
| Orbit rate, no load | 3000 - 9000 rpm |
| Cable length | 4,0 m |
| Cable type | PUR |
| Dimensions WxLxH | 370 x 40 x 140 mm |
| Weight | 2,4 kg |

Standard equipment

- 1 Special hook-and-loop pad, cushioned (487953)
- 1 Special hook-and-loop pad, cushioned (487988)