

IW 1/2" 750 18.0-EC

Cordless impact wrench 18,0 V

Order no. 530232

GTIN 4030293242425



- + Brushless motor with greater efficiency and a longer service life
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Tool holder square drive for 1/2" impact sockets.
- + Electronic quick-acting brake
- + Damping element separates hand grip from motor, bringing significant reduction in vibration transmission
- + Powerful impact mechanism for maximum performance enables for example stuck or rusted screw connections to be loosened even in extreme applications
- + Speed command: Possibility of setting three different speed ranges for different applications and controlled tightening or loosening
- + Accelerator trigger with lock-off switch
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs. Delivery does not include battery and charger
- + Right/left rotation with safety catch
- + Auto-Stop mode: When tightening, the machine stops as soon as the blow starts. When loosening, the machine stops as soon as the blow stops. Suitable to prevent over-tightening of the screw or nut.
- + Compact design with die-cast aluminium machine head. Extremely durable and impact-resistant



Technical data

Battery voltage	18.0 V
Battery capacity	2.5 / 5.0 / 8.0 Ah
Torque settings	3 Steps
Max. torque, setting 1	150 Nm
Max. torque, setting 2	200 Nm
Max. torque, setting 3	750 Nm
Max. loosening torque	950 Nm
No-load speed, 1st gear	0 - 500 rpm
No-load speed, 2nd gear	0 - 1000 rpm
No-load speed, 3rd gear	0 - 2100 rpm
No-load blows, setting 1	0 - 1000 1 rpm
No-load blows, setting 2	0 - 2000 1 rpm
No-load blows, setting 3	0 - 2450 1 rpm
Tool holder, impact drill	1/2" outside
Dimensions WxLxH	159 x 74 x 227 mm
Weight without battery pack	1.9 kg

Standard equipment

- 1 Belt clip (430714)
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (531322)