

LD 24-6 180, Kit TH-Jet

Grinding machine for large areas, 180 mm

Order no. 418870

GTIN 4030293184442



- + Flexible rubber vacuum ring with low-wear metal ring: moves smoothly over the surface and protects against dust and flying stones
- + Vacuum dust collection: protects against abrasive dust, reduces disc wear, keeps concrete pores for the new coat open
- + Soft-start: for a soft start without power overloading
- + Restart protection after power interruption
- + Extraction hood: with stepless height adjustment
- + Vacuum attachment: 32 mm exterior Ø
- + Spindle lock
- + Ideal for large areas
- + Optimum guidance by rear shaft handle
- + With steplessly adjustable, vibration-proof, ergonomic bail handle, for optimum handling and machine control
- + Suction hose/adapter not included in delivery package
- + Sanding plates of heights 22 mm to 28 mm are suitable
- + Diamond grinding disc suitable for grinding concrete parts, roughing old weathered concrete, hard cement plaster, removing shuttering protrusions and concrete runs, hardened epoxy resin coatings and the natural sintering on concrete components. High grinding capacity and service life from the innovative segment design. Optimal ground preparation for further coating.



Technical data

| | |
|---------------------------------|--------------------|
| Power consumption | 2400 W |
| Power output | 1450 W |
| Voltage | 230 V |
| Frequency | 50/60 Hz |
| Disc diameter | 180 mm |
| Tool holder, renovation grinder | M14 |
| Cable length | 4.0 m |
| Dimensions WxLxH | 570 x 240 x 140 mm |
| Weight | 6.6 kg |

Standard equipment

- 1 Thermo-Jet diamond grinding disc (359386)
- 1 Guard with rubber extraction ring (421154)
- 1 Adapter (445142)
- 1 Clamping nut M 14 (100080)
- 1 Clamping flange, SW 17 (191604)
- 3 Cable clip (302538)
- 1 Hexagon socket wrench, SW 6 (256832)
- 1 Face pin spanner (392537)
- 1 Carrying case (444391)
- 1 Bail handle