

## BRE 8-4 INOX Set

Pipe belt sander and belt file TRINOXFLEX Set

Order no. 453463

GTIN 4030293201088



- + Microprocessor control: speed selection, tachogenerator constant speed control, soft start, restart protection after power failure, overload protection and temperature monitoring
- + Unique tool attachment with quick-action coupling for tool-free changing of the system attachments for burnishing, pipe belt sanding, filing
- + Completely cast electronic components prevents damage due to metal dust. The 3-fold winding protection reduces motor wear, increases service life
- + Sanding belt replacement: quick and tool-free
- + Sanding belt dimension: 533 x 4 - 30 mm
- + High-quality, spring-mounted sanding arm: light alloy with 2 deflection rollers. For optimum wrap-round on pipes, up to max. 270°
- + Spindle lock



### Technical data

Power consumption	800 W
Power output	425 W
Voltage	230 V
Frequency	50/60 Hz
Belt speed	3 - 8 m/sec
No-load speed	1400 - 4000 rpm
Belt length	533 mm
Belt width	4/9/30 mm
Suitable for max. pipe diameter	50 mm
Cable length	4.0 m
Dimensions WxLxH	320 x 210 x 195 mm
Weight	2.6 kg

### Standard equipment

- 1 Sanding attachment, pipe belt (459585)
- 1 Sanding attachment, belt file (459593)
- 1 Interchangeable roller set (459607)
- 2 Sanding belt ZIRCOFLEX (303615)
- 2 Sanding belt ZIRCOFLEX (303623)
- 2 Sanding belt ZIRCOFLEX (257105)
- 2 Sanding belt ZIRCOFLEX (257102)
- 2 Sanding belt ZIRCOFLEX (255328)
- 2 Sanding belt ZIRCOFLEX (255329)
- 1 Sanding belt MESHFLEX (318663)
- 1 Sanding belt MESHFLEX (318647)
- 1 Side handle, red (194034)
- 1 Hexagon socket wrench (102229)
- 1 Hexagon socket wrench, SW 5 (115460)
- 1 Hexagon socket wrench, SW 6 (104167)
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (457337)