

# IW 1/2" 950 18.0-EC 5.0/ Set

**Cordless impact wrench 18,0 V**

**Order no. 530187**

**GTIN 4030293242234**



- + Brushless motor with greater efficiency and a longer service life
- + Electronic management system (EMS) protects the machine, extends the service life, and increases efficiency
- + Tool holder square drive for 1/2" impact sockets.
- + Electronic quick-acting brake
- + Damping element separates hand grip from motor, bringing significant reduction in vibration transmission
- + Powerful impact mechanism for maximum performance enables for example stuck or rusted screw connections to be loosened even in extreme applications
- + Speed command: Possibility of setting three different speed ranges for different applications and controlled tightening or loosening
- + Accelerator trigger with lock-off switch
- + Reinforced die-cast aluminium gear housing with the greatest wall thickness in its class
- + With battery protection element to prevent damage to the battery pack when putting it down
- + Ergonomically designed, non-slip, soft grip handle
- + Integrated LED lamp with persistence function
- + LED battery capacity display
- + FLEX battery system: suitable for all FLEX 18 V battery packs



## Technical data

|                             |                    |
|-----------------------------|--------------------|
| Battery voltage             | 18.0 V             |
| Battery capacity            | 2.5 / 5.0 / 8.0 Ah |
| Torque settings             | 3 Steps            |
| Max. torque, setting 1      | 280 Nm             |
| Max. torque, setting 2      | 700 Nm             |
| Max. torque, setting 3      | 950 Nm             |
| Max. loosening torque       | 1580 Nm            |
| No-load speed, 1st gear     | 0 - 500 rpm        |
| No-load speed, 2nd gear     | 0 - 1000 rpm       |
| No-load speed, 3rd gear     | 0 - 2100 rpm       |
| No-load blows, setting 1    | 0 - 1000 1 rpm     |
| No-load blows, setting 2    | 0 - 2000 1 rpm     |
| No-load blows, setting 3    | 0 - 2450 1 rpm     |
| Tool holder, impact drill   | 1/2" outside       |
| Dimensions WxLxH            | 222 x 77 x 240 mm  |
| Weight without battery pack | 3.1 kg             |

## Standard equipment

- 1 Rapid charger (417882)
- 1 Carrying case L-BOXX® (414085)
- 1 Case insert (493996)
- 2 Li-Ion rechargeable battery pack 18,0 V (532733)